Hand Operated Curtain Track Systems








Hand Operated Curtain Track

Silent Gliss 1060



Product Information



3

- Hand operated curtain track for light curtains in residential and contract applications.
- For light weight curtains.
- Very elegant, thin and bendable profile (Min. radius 2.36").
- Easy fixing with hidden clamp to all kind of ceilings.
- Standard colours: anodised aluminium or white powder coated.
- Standard length of the profiles is 236". Systems can be planned to unlimited lengths due to a special connecting bridge.
- Large and attractive fabric offer.
- Snake Wave Capable

When splicing on a gradual curve, each side of the track by the splice must have a straight piece of profile of 2" on both Sides (totaling 4" of straight profile)

Silent Gliss®

Profile and Bending Information






Fitting Information



Fitting Options

CAD download through Silent Gliss

Ceiling fixing with clamp 3060





Fix track with at least one clamp 3060 every 11" - 15.7" . Higher edge of profile to room side. The final distances depend on system height and width and the way of confectioning.



Standard Accessories

3070	End stop	3085	Spring stop	
3533	Glider	3599	Hook	


Optional Accessories

3534	Glider 3533 in strip form	3537	Glider	
3548	Clic-Glider	3549	Clic-Hookglider	
3582	Hook	3598	E yel et	

Useful Measurements (Metric)

3061 Endcover

3062 Connecting bridge



1060



www.SilentGlissAmerica.com
Silent Gliss Inc United States Distribution
755 East 134th street, 3rd Floor.
Bronx, NY 10454

Correspondence: P.O. Box 592 New York, Ny 10150

Please call or email with any questions or for technical catalogs: info@SilentGlissAmerica.com
Tel: 718-412-9040